
TECHNICAL DATA SHEET

FP SA4LS



Description:
Ø6.3 x Lmm, Self-drilling, Bi-metal stainless steel, Stitcher

Fastener Material:
Austenitic Stainless Steel A4 (316 Grade)

Drill Point:
Hardened Carbon Steel

Drilling Capacity:
0.4mm – 2 x 0.9mm


Washer Material:
1.0mm Austenitic Stainless Steel A4 (316 Grade)

EPDM Thickness:
S16 – 2.5mm / S19 – 3.0mm / S29 – 3.0mm

EPDM Hardness:
50° Shore


Head Styles & Drive:

SA4LS	8.0mm Hex with plain finish
SA4PCTS	8.0mm Hex with P.P.C. finish
SA4CTS	11.0mm Bi-hex nylon moulded finish



Application(s):
Sheet to sheet sidelap
Tail stitcher
Flashing to sheet

Code	Length	Effective Thread Length
SA4LS225	25mm	5mm



Effective Thread Length includes the maximum substrate thickness and ensures that only stainless threads are engaged.

Code Explanation

SA4 LS 25 S16

SA4	=	A4 (316 Grade) Stainless Steel Fastener
LS	=	Stitcher
25	=	Fastener Length
S16	=	16mm Stainless Steel Bonded Washer

10A05 SA4CT S 25 S19

10A05	=	Colour Reference
SCT	=	Bi-hex Nylon Moulded A4 (316 Grade)Stainless Steel Fastener
S	=	Stitcher
25	=	Fastener Length
S19	=	19mm Stainless Steel Bonded Washer

T +44 (0) 1242 265100 **E** info@fixingpoint.com **fixingpoint.com**

Reg No: 02050516 • Reg Co address: 183 - 205 Westgate Street, Gloucester, England, GL1 2RN

Revision: 1.0 | Date: November 2026

TECHNICAL DATA SHEET

FP SA4LS


Durability:
These products may be used for indoor and outdoor applications with corrosion category class of C1 – C4 in accordance with Table B1 and Table B2 in EN 1993-1-3 and EN ISO 12944-2. Subject to approval by Fixing Point, they may also be used in applications with a corrosion category class C5 in accordance with these Tables.

Warranties up to 40-years on these products are available with prior project approval from Fixing Point.

Note: These products are not considered suitable for use in swimming pool buildings where they may be exposed to a chlorine-rich environment and the risk of condensation – consult Fixing Point


Technical Data:

Pull Out




Material Thickness	0.5mm	0.7mm
Grade	S220	
Pull Out (kN)	0.600	0.929

Pull Through




Washer	S16		S19	
Material Grade Thickness	Steel S220 0.5mm	Aluminium 170N/mm² 0.9mm	Steel S220 0.5mm	Aluminium 170N/mm² 0.9mm
Pull Through (kN)	1.73	1.82*	1.87	1.97*

Shear



Sheet - Material Grade Thickness	Steel S220 0.5mm
Purlin / Rail - Material Grade Thickness	Steel S220 0.5mm
Shear (kN)	0.98



Ultimate Tensile (kN)	Ultimate Shear (kN)
11.16	11.01



All values shown are Characteristic value (NRk & VRk). The values have been derived from methodology as defined in the European Assessment Document (EAD) 33046-01-0602. To determine the Design Value (NRd & VRd) the material safety factor of 1.33 must be applied to the Characteristic Values – unless a greater safety factor is specified.

Values marked * are interpolated.

Installation Guidelines:
Self-drilling fasteners should always be installed with a dedicated variable speed screwgun, fitted with an appropriately adjusted depth locating nosepiece. This will ensure that the correct compression of the washer is achieved.

Under no circumstances should impact drivers be used to install self-drilling fasteners they are detrimental to the mechanical performance of the fastener.

Based upon industry standards the following washer diameters should be used for the following applications:



Roof Primary / Main-fix = 19mm
Rooflight Primary / Main-fix = 29mm
Wall Primary / Main-fix = 16mm
Roof, Rooflight & Wall Secondary / Stitcher = 16mm

As well as choosing the appropriate washer diameter, the EPDM thickness and shore hardness is equally as important. It is recommended that for composite panels a minimum 3.0mm EPDM with a Shore hardness of between 40-60 and for built-up systems a minimum EPDM thickness of 2.0mm and Shore hardness of 60-80.