
TECHNICAL DATA SHEET

FP+ XSDHT





Description:
Ø5.5/6.3mm x Lmm, Self-drilling, Bi-metal stainless steel, Composite Panel, Light Section

Fastener Material:
Austenitic Stainless Steel A2 (304 Grade)

Drill Point:
Hardened Carbon Steel

Drilling Capacity:
1.2mm – 3.0mm

Washer Material:
1.0mm Austenitic Stainless Steel A2 (304 Grade)

EPDM Thickness:
S16 – 2.5mm / S19 – 3.0mm / S29 – 3.0mm


EPDM Hardness:
50° Shore

Head Styles & Drive:

XSDHT	8.0mm Hex with plain finish
XSPCTHT	8.0mm Hex with P.P.C. finish
XSCTHT	11.0mm Bi-hex nylon moulded finish

Application(s):
Composite panel to light section rail

Certifications:
CE
ETA 23/0661



Code	Length	Minimum (Panel)	Maximum Incl. Purlin
XSDHT065	65mm	30mm	45mm
XSDHT080	80mm	40mm	60mm
XSDHT110	110mm	35mm	90mm
XSDHT125	125mm	50mm	105mm
XSDHT150	150mm	75mm	130mm
XSDHT180	180mm	105mm	160mm

Code	Length	Minimum (Panel)	Maximum Incl. Purlin
XSDHT200	200mm	125mm	180mm
XSDHT230	230mm	155mm	210mm
XSDHT250	250mm	175mm	230mm
XSDHT275	275mm	200mm	255mm
XSDHT300	300mm	225mm	280mm


Code Explanation

XSD HT 150 S19

XSD	=	FP+ Stainless Steel Light Section Fastener
HT	=	High Thread / Composite Panel
150	=	Fastener Length
S19	=	19mm Stainless Steel Bonded Washer

10A05 XSCT HT 125 S16

10A05	=	Colour Reference
XSCT	=	FP+ Bi-hex Nylon Moulded Stainless Steel Light Section Fastener
HT	=	High Thread / Composite Panel
125	=	Fastener Length
S16	=	16mm Stainless Steel Bonded Washer



Maximum dimension includes the maximum substrate thickness and ensures that only stainless threads are engaged.

T +44 (0) 1242 265100 **E** info@fixingpoint.com **fixingpoint.com**

Reg No: 02050516 • Reg Co address: 183 - 205 Westgate Street, Gloucester, England, GL1 2RN

Revision: 1.0 | Date: December 2025

Everything on point

TECHNICAL DATA SHEET

FP+ XSDHT


Durability:
With reference to ETA 23/0661, these products may be used for indoor and outdoor applications with corrosion category class of C1, C2 or C3 in accordance with Table B1 and Table B2 in EN 1993-1-3 and EN ISO 12944-2. Subject to approval by Fixing Point, they may also be used in applications with a corrosion category class C4 or C5 in accordance with these Tables.

Warranties up to 40-years on these products are available with prior project approval from Fixing Point.

Note: These products are not considered suitable for use in swimming pool buildings where they may be exposed to a chlorine-rich environment and the risk of condensation – consult Fixing Point


Technical Data:

Pull Out




Material Thickness	1.2mm	1.4mm	1.5mm	1.8mm	2.0mm	2.5mm	3.0mm
Grade	S450						
Pull Out (kN)	1.460	2.179*	2.538	3.679*	4.440	5.590*	6.740

Pull Through



Washer	S16		S19	
Material Grade Thickness	Steel S220 0.5mm	Aluminium 170N/mm² 0.9mm	Steel S220 0.5mm	Aluminium 170N/mm² 0.9mm
Pull Through (kN)	1.98	1.97*	2.26	2.25*

Shear



Sheet - Material Grade Thickness	Steel S220 0.4mm
Purlin / Rail - Material Grade Thickness	Steel S450 1.2mm
Shear (kN)	0.76



Characteristic Tensile (kN)
10.107



Characteristic Shear (kN)
9.758

All values shown are Characteristic value (NRk & VRk). The values have been derived from methodology as defined in the European Assessment Document (EAD) 33046-01-0602 specific to the ETA 23/0661 noted above. To determine the Design Value (NRd & VRd) the material safety factor of 1.33 must be applied to the Characteristic Values – unless a greater safety factor is specified.

Values marked * are interpolated.

Installation Guidelines:
Self-drilling fasteners should always be installed with a dedicated variable speed screwgun, fitted with an appropriately adjusted depth locating nosepiece. This will ensure that the correct compression of the washer is achieved.

Under no circumstances should impact drivers be used to install self-drilling fasteners they are detrimental to the mechanical performance of the fastener.

Based upon industry standards the following washer diameters should be used for the following applications:



Roof Primary / Main-fix = 19mm
Rooflight Primary / Main-fix = 29mm
Wall Primary / Main-fix = 16mm
Roof, Rooflight & Wall Secondary / Stitcher = 16mm

As well as choosing the appropriate washer diameter, the EPDM thickness and shore hardness is equally as important. It is recommended that for composite panels a minimum 3.0mm EPDM with a Shore hardness of between 40-60 and for built-up systems a minimum EPDM thickness of 2.0mm and Shore hardness of 60-80.