
TECHNICAL DATA SHEET

FP+ XSLP4

Description:
Ø5.5 x Lmm, Self-drilling, Bi-metal stainless steel, Light Section

Fastener Material:
Austenitic Stainless Steel A2 (304 Grade)

Drill Point:
Hardened Carbon Steel

Drilling Capacity:
1.2mm – 3.0mm

Washer Material:
1.0mm Austenitic Stainless Steel A2 (304 Grade)

EPDM Thickness:
S12 – 2.5mm


EPDM Hardness:
50° Shore


Head Styles & Drive:

XSLP4	10.5mm Low Profile with plain finish
XSLP4+COL	10.5mm Low Profile with P.P.C. finish

Application(s):
Single Skin to light section rail
Weather sheet to Spacer support rail


Certifications:
CE
ETA 23/0660







Code	Length	Effective Thread Length
XSLP438	38mm	18mm
XSLP450	50mm	30mm
XSLP480	80mm	60mm



Effective Thread Length includes the maximum substrate thickness and ensures that only stainless threads are engaged.

Code Explanation

XSLP 4 38

XSLP	=	FP+ Stainless Steel Low Profile Fastener
4	=	Light Section
38	=	Fastener Length

* Supplied standardly with a 12mm stainless bonded washer

XSLP 4 80 10A05

10A05	=	Colour Reference – Suffix the code with the colour signifies a P.P.C. Head
XSLP	=	FP+ Stainless Steel Low Profile Fastener
4	=	Light Section
80	=	Fastener Length

* Supplied standardly with a 12mm stainless bonded washer

TECHNICAL DATA SHEET

FP+ XSLP4


Durability:
With reference to ETA 23/0660, these products may be used for indoor and outdoor applications with corrosion category class of C1, C2 or C3 in accordance with Table B1 and Table B2 in EN 1993-1-3 and EN ISO 12944-2. Subject to approval by Fixing Point, they may also be used in applications with a corrosion category class C4 or C5 in accordance with these Tables.

Warranties up to 40-years on these products are available with prior project approval from Fixing Point.

Note: These products are not considered suitable for use in swimming pool buildings where they may be exposed to a chlorine-rich environment and the risk of condensation – consult Fixing Point


Technical Data:

Pull Out




Material Thickness	1.2mm	1.5mm	1.8mm	2.0mm	2.5mm	3.0mm
Grade	S450					
Pull Out (kN)	1.460	2.578*	3.695*	4.440	5.590*	6.740

Pull Through




Washer	S12	
Material Grade Thickness	Steel S220 0.5mm	Aluminium 170N/mm² 0.9mm
Pull Through (kN)	1.34	1.33*


Shear



Sheet - Material Grade Thickness	Steel S220 0.5mm		
Purlin / Rail - Material Grade Thickness	Steel S450 1.2mm	Steel S450 2.0mm	Steel S450 3.0mm
Shear (kN)	1.51	1.46	1.48



Ultimate Tensile (kN)	Ultimate Shear (kN)
10.901	7.797



All values shown are Characteristic value (NRk & VRk). The values have been derived from methodology as defined in the European Assessment Document (EAD) 33046-01-0602. To determine the Design Value (NRd & VRd) the material safety factor of 1.33 must be applied to the Characteristic Values – unless a greater safety factor is specified.

Values marked * are interpolated.

Installation Guidelines:
Self-drilling fasteners should always be installed with a dedicated variable speed screwgun, fitted with an appropriately adjusted depth locating nosepiece. This will ensure that the correct compression of the washer is achieved.

Under no circumstances should impact drivers be used to install self-drilling fasteners they are detrimental to the mechanical performance of the fastener.

Based upon industry standards the following washer diameters should be used for the following applications:



Roof Primary / Main-fix = 19mm
Rooflight Primary / Main-fix = 29mm
Wall Primary / Main-fix = 16mm
Roof, Rooflight & Wall Secondary / Stitcher = 16mm

As well as choosing the appropriate washer diameter, the EPDM thickness and shore hardness is equally as important. It is recommended that for composite panels a minimum 3.0mm EPDM with a Shore hardness of between 40-60 and for built-up systems a minimum EPDM thickness of 2.0mm and Shore hardness of 60-80.